SCHMITZ

TSF

COUNT ON IT.



SCHMITZ FEUERWEHRTECHNIK

Fire-fighting technology geared to customers' needs.

At Schmitz, we are committed to delivering the very best in fire-fighting technology – fully compliant with all relevant standards and precisely tailored to our customers' requirements. We achieve this through close collaboration: from the initial needs analysis and planning stage through to production and beyond.

As an owner-managed German family business, we act independently – free from corporate group structures, political influence and external investors. This freedom enables us to make swift decisions and focus consistently on what matters most: our customers' needs.

Our industry specialists work closely together across five sites in Germany and Croatia. Behind every one of our fire-fighting vehicles is a dedicated, professional team that continually strives for improvement, optimises processes and expands its expertise.

We do not rest on our achievements. Our vehicles are built precisely in line with individually agreed loading plans – ensuring maximum functionality in operation. The result: Vehicles that fit the brief exactly.
Made in Germany.

Built with responsibility. For those who carry responsibility.
Count on it.

TSF

Pumper TSF

further information
on the vehicle

Technical data

Chassis	Iveco Daily 70C 18H 4x2 - Euro 6e
Cabin	Driver and crew compartment (1+5) • Original Iveco double cab, second row with four original seats in the driving direction
Body	Schmitz aluminium lightweight construction • 5-part body made of high-quality anodised aluminium • Two equipment compartments with aluminium roller shutters on each side, additional equipment compartment with rear shutter • Robust roof made of aluminium chequer plate
Control system	Inomatic® control (CAN bus control unit)
Pump	PFPN 10-1000
Extinguishing technology	The Schmitz three-way switching unit permits smooth switching between suction operation and tank operation
Standard	as per DIN 14530-16
Tank	up to 1,000 L water
Equipment load	Standard equipment load as per Table 1 Optional: fastenings for additional equipment as per DIN 14800-18
Lighting	Light mast for up to 4 floodlights Ambient lighting: peripheral LED light strip
Dimensions	L 6,000 mm x W 2,300 mm x H 2,600 mm
Wheelbase	4,350 mm
Permissible total weight	4,750 kg
Optional	2 compressed air breathing apparatuses

Site Farnstädt
Schmitz Feuerwehrtechnik GmbH

Unterm Weinberg 5
06279 Farnstädt, Germany
Tel.: +49 34776 9176-0
E-Mail: info@schmitz-feuerwehr.de

Site Nobitz
Schmitz Feuerwehrtechnik Nobitz GmbH

Laupheimer Str. 1
04603 Nobitz, Germany
Tel.: +49 3447 510848-0
E-Mail: info@schmitz-feuerwehr.de

it's SCHMITZ

SCHMITZ